Xerox[®] AltaLink[®] Colour Multifunction Printers

Xerox[™]

C8130/C8135/C8145/C8155/C8170



Xerox® AltaLink® C8100 Series Colour Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.co.uk.

System Specification	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170	
Speed ¹						
Colour/Black and White	Up to 30/30 ppm	Up to 35/35 ppm	Up to 45/45 ppm	Up to 55/55 ppm	Up to 70/70 ppm	
Monthly Duty Cycle ²	Up to 90,000 pages	Up to 110,000 pages	Up to 200,000 pages	Up to 300,000 pages	Up to 300,000 pages	
Hard Drive/Processor/ Memory	Minimum 128 GB SSD/ Optic	onal: 500 GB HDD/Intel Atom	[®] Quad Core 1.91 GHz/4 GB syst	em memory (8 GB system mer	nory AltaLink® C8170)	
Connectivity	Ethernet 10/100/1000 Base- (iBeacon)	T, High-speed USB 2.0 direct p	orint, NFC, Optional: WiFi/WiFi [Direct with Xerox® Dual Band W	/ireless Kit, Bluetooth	
Controller Features	Configuration Cloning, Config	guration Watchdog, Fleet Orch	estrator, Remote Control Panel,	Unified Address Book		
Optional Controller	Xerox® EX-c C8100 Print Serv	er Powered by Fiery®				
Copy and Print						
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; P	Print: Up to 1200 x 2400 dpi				
First-Print-Out Time (as fast as)	5.7 seconds colour/4.2 secon	ds black and white	4.9 seconds colour/ 3.8 seconds black and white	4.5 seconds colour/ 3.2 seconds black and white	3.8 seconds colour/ 3.0 seconds black and white	
First-Copy-Out Time (as fast as) (from platen/ warmed-up state)	6.1 seconds colour/4.5 seconds black and white		5.5 seconds colour/ 4.4 seconds black and white	4.7 seconds colour/ 3.7 seconds black and white	4.0 seconds colour/ 3.2 seconds black and white	
Page Description Language	Adobe® PostScript® 3™, Adob	pe® PDF, PCL® 5c/PCL® 6				
Print Features	marking and infrared detecti Repositories (Dropbox, OneD	on technology, Job Identificat Irive and Google Drive), Print fr	et Layout, Encrypted Secure Prin ion, Job Monitoring, Long Sheet iom USB, Print on Alternate Pap ptional: Print from and Scan to J	(Banner) Printing, Print Arounc er, Scaling, Store and Recall Dri	I, Print from Cloud ver Settings, Two-sided	
Mobile and Cloud ready						
Mobile Connectivity	Near Field Communication (I	NFC); Optional: Wi-Fi Direct, V	Vi-Fi (802.11 b/g/n/ac), AirPrint	(iOS) including iBeacon (Blueto	oth)	
Mobile Printing	Mopria® Scan, Apple AirPrint (iOS) including iBeacon (Blue		d), @PrintByXerox App; Optiono	ı l: Xerox [®] Workplace Mobile Ap	p (iOS/Android), AirPrint™	
Mobile Scanning	Mopria® Scan, Apple AirPrint	™, Optional: Xerox® Workplace	Mobile App (iOS/Android)			
Mobile Apps and Xerox App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalise, print, convert, route, collaborate and communicate. Visit www.xerox.co.uk/en-gb/connectkey/workplace-apps to find apps by industry or workflow. Software and services: Xerox® DocuShare® (xerox.co.uk/ecm), XMPie® (www.xerox.co.uk/en-gb/digital-printing/workflow-software/printing-software/xmpie-personalised-communication-software), Xerox® Workplace Solutions (www.xerox.co.uk/en-gb/office/print-management-solutions)					
Xerox® Workplace Central Platform	One-platform consistency for seamless productivity across computers, mobile devices and printers. With Workflow Central's ever-expanding suite of cloud-based workflows, you can change documents into audio files for easy listening, convert PDF or image files to popular Microsoft formats for shareability with a wider audience, turn handwriting into legible, editable and shareable text, translate to/from over 40 different languages and automatically redact Personal Identifiable Information using set words or phrases					

Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional: Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and a cloud-based version (Workplace Cloud) of this solution
Cloud Identity Provider (IdP) Integration	Use your desktop, laptop or mobile login credentials to log in to your AltaLink® MFPs with direct connections to popular cloud identity providers Okta, Ping Identity and Microsoft® Azure
Scan	
Standard Features	Destinations: Scan to USB/PC via USB port/Email/Network (FTP/SMB), HTTP, HTTPS, SFTP destinations; File Formats: PDF, PDF/A, JPEG, TIFF; Convenience Features: 1-Touch Apps, Imaging Security with AltaLink's proprietary marking and infrared detection technology, Optical Character Recognition (OCR), Password-protected PDF, Scan Preview, Scan to Folder, Scan to Home, Searchable PDF, Single/Multi-Page PDF/TIFF, Touchless Workflow Accelerators, TWAIN Support, Unified Address Book
Optional Features	Scan to Cloud Repositories (Dropbox, OneDrive and Google Drive). Xerox® Scanning App for DocuShare®, other solutions available through various Xerox® Business Innovation Partners at www.xerox.co.uk/en-gb/office/printer-software , Print from and Scan to Xerox® DocuShare® Go content management
Fax	
Standard Features	Fax Build Job, Network Server Fax Enablement
Optional Features	Walk-up Fax (one-line and two-line options available, includes LAN Fax, Direct Fax, Fax Forward to Email or SMB Share)
Security	
Standard Features	802.1x, Access Control, Audit Log, Automated threat response through Trellix DXL*/Cisco® pxGrid integration, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) Integration, Common Criteria Certification (ISO 15408), Configuration Watchdog, Encrypted Secure Print, Encrypted Storage Drive (AES 256-bit, FIPS 140-3), FIPS 140-3, Firmware Verification, HTTPS, Imaging Security (copy, print, scan, email) with AltaLink's proprietary marking and infrared detection technology, IPsec, Job Level Encryption via HTTPS and Drivers, Local Authentication (Internal Database), Trellix Embedded Control Whitelisting*, Trellix ePolicy Orchestrator®*, Network Authentication, Port/IP/Domain Filtering, Security Certificates utilising ECDSA, Security Dashboard, SFTP and Encrypted Email, SHA-256 Hash Message Authentication, SIEM integration (Splunk, LogRhythm, Trellix ESM*), Signed Email, SNMPv3, TLS1.1/1.2/1.3, TPM, Trusted Boot, User Access and Internal Firewall, User Permissions
Optional Features	Trellix Integrity Control*, Smart Card Enablement Kit (CAC/PIV/.NET)³, Xerox® Integrated RFID Card Reader, Encrypted Hard Disk (AES 256-bit, FIPS 140-3) with multi-pass Image Overwrite³, Xerox® Workplace Cloud/Suite Print Management and Content Security; WPA2 and WPA3 with Dual Band Wireless Kit; learn more at www.xerox.co.uk/en-gb/office/print-management-solutions
Print Management	
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement
Optional Features	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox® Business Innovation Partners. Xerox® Virtual Print Management Service; learn more at www.xerox.co.uk/en-gb/office/printer-software#printmanagement

Features and Accessories

Single-Pass Duplex Automatic Document Feeder (DADF)

saves time by simultaneously scanning both sides of $\boldsymbol{\alpha}$ document with up to 270 impressions per minute (ipm).



USER INTERFACE



Intuitive Tablet-like 10.1-inch Colour Touchscreen is

customisable and lets you perform tasks in just a few taps. Try it out at xerox.com/AltaLink8100UI.

PAPER INPUT⁴

Two 520-sheet Adjustable Trays (common with all configurations). Tray 1 handles media sizes up to A3 and Tray 2 handles media sizes up to SRA3.



Envelope Kit (optional – replaces Tray 1) provides feeding of up to 60 envelopes.



High Capacity Tandem Tray Configuration holds a total paper capacity of up to 3,140 sheets.

Four Tray Module Configuration (available for C8130/C8135) holds a total of up to 2,180 sheets.

Bypass Tray handles up to 100 sheets; Custom sizes: 89 x 98 mm to 320 x 1 320 mm



High Capacity

Feeder (optional) holds 3,000 sheets of A4 paper, increasing the maximum paper capacity to 6.140 sheets.



LONG SHEET PRINTING

Long Sheet Feed Kit (optional) provides the ability to print up to 320 x 1,320 mm media



INNOVATIVE TECHNOLOGIES



Xerox® Integrated RFID Card Reader (optional) adds card-based authentication with support for over 90 access cards.



Near Field Communication (NFC) Tap-to-Pair allows users to tap their mobile devices to the AltaLink® C8100 Series user panel and quickly connect with the multifunction printer.



Smart Proximity Sensor detects when users are nearby. It conserves energy during inactive periods and automatically activates the device when a user approaches.

PAPER OUTPUT/FINISHERS⁴



(optional) provides advanced finishing functions, optional crease/score and saddle-stitch booklet, capable of 60-page booklets (2 to 15 sheets).

Office Finisher



C-Fold/Z-Fold Unit (optional) adds C-fold,

Z-fold and Z-half-fold capability to the BR Finisher or BR Booklet Maker Finisher



BR Booklet Maker

Finisher (optional) creates 64-page saddle-stitched booklets (2 to 16 sheets).



Dual Offset Catch Tray

(available when no finishers are installed; Single Offset Catch Tray with finishers).



Integrated Office Finisher

(optional with C8130/C8135/ C8145/C8155) provides 500-sheet stacking and 50-sheet, 2-position stapling.



Convenience Stapler

(optional) staples up to 50-sheets of 75 gsm media.

Device Specification							
Control Panel Languages		US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic					
Accessories							
Optional	Convenience Stapler (include Envelope Tray (Replaces Tray Foreign Device Interface (Als readers High Capacity Feeder 3000 A Hole Punch (2/3, 2/4, Swedis! Horizontal Transport Kit Integrated Office Finisher (Av Long Sheet Feed Kit (banner Trellix Integrity Control Enab Multi-feed Detection Kit (Alto Office Finisher Scan To Cloud Enablement Kit Smart Card Enablement Kit ³ Unicode Font Kit USB Keyboard/Shelf Kit Walk-up Fax (One- or Two-lin- Wi-Fi/Wi-Fi Direct with Dual I Xerox® EX-c C8100 Print Serv Xerox® Integrated RFID Card	(requires Horizontal Transport equires Horizontal Transport surfaces) 1) o known as Auxiliary Access (4 h) railable with AltaLink® C813 printing) lement Kit* aLink® C8170 only) it e options, includes LAN Fax) Band Wireless Kit er Powered by Fiery® Reader Kit	Kit) C-fold/Z-fold Unit for BR Device Interface) for third-po	Finisher or BR Booklet Maker Fi arty access control devices, such	n as coin machines and card		
Electrical Requirements	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltαLink® C8170		
North America	Voltage: 110-127 VAC +/- 10 Frequency: 50/60 Hz +/- 3%,				Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 20 A		
Europe	Voltage: 220-240 VAC +/- 10 Frequency: 50/60 Hz +/- 3%,				Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 10 A		

Device Specification (conti	nued)				
Power Consumption	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltαLink® C8155	AltaLink® C8170
Running (Average)	115 V: 576 watts 230 V: 586 watts	115 V: 600.3 watts 230 V: 595.8 watts	115 V: 717 watts 230 V: 674 watts	115 V: 806 watts 230 V: 760 watts	115 V: 929 watts 230 V: 908 watts
Standby Mode	115 V: 67 watts 230 V: 71 watts	115 V: 64 watts 230 V: 70 watts	115 V: 71 watts 230 V: 71 watts	115 V: 72 watts 230 V: 70.3 watts	115 V: 91.1 watts 230 V: 79 watts
Auto Off/Sleep Mode	115 V: 0.69 watts 230 V: 0.71 watts (Default time to sleep mode = 0 minutes)	115 V: 0.69 watts 230 V: 0.72 watts (Default time to sleep mode = 0 minutes)	115 V: 0.67 watts 230 V: 0.71 watts (Default time to sleep mode = 0 minutes)	115 V: 0.67 watts 230 V: 0.71 watts (Default time to sleep mode = 0 minutes)	115 V: 0.68 watts 230 V: 0.75 watts (Default time to sleep mode = 0 minutes)
Warm-up (from Off)	As fast as 8.5 seconds				
Recovery from Sleep	As fast as 4.5 seconds				
Operating Environment					
Required Temperature Range	10 to 28 °C				
Required Relative Humidity	15% to 85%				
Sound Power Levels	Operating: 63.7/64.2 dB(A) Standby: 4.0/4.0 dB(A)		Operating: 65.2/67.3 dB(A) Standby: 4.3/4.3 dB(A)		Operating: 70.4 dB(A) Standby: 4.3 dB(A)
Dimensions and Weight					
Base Configuration	Width: 620 mm Depth: 723 mm Height: 1,130 mm Weight: 143.1 kg				Width: 620 mm Depth: 793 mm Height: 1,169 mm Weight: 159.7 kg
With Integrated Office Finisher (C8130, C8135, C8145, C8155)	Width: 819 mm Depth: 723 mm Height: 1,130 mm Weight: 154.2 kg				N/A
With Office Finisher (with Booklet Maker)	Width: 1,207 mm Depth: 723 mm Height: 1,130 mm Weight: 182.5 kg				Width: 1207 mm Depth: 793 mm Height: 1,169 mm Weight: 199 kg
Base Configuration with Business Ready (BR) Finisher	Width: 1,395 mm Depth: 723 mm Height: 1,130 mm Weight: 187 kg				Width: 1,395 mm Depth: 723 mm Height: 1,169 mm Weight: 203.4 kg
Base Configuration with BR Booklet Maker Finisher	Width: 1,496.3 mm Depth: 723 mm Height: 1,130 mm Weight: 204 kg				Width: 1,496.3 mm Depth: 723 mm Height: 1,169 mm Weight: 220.6 kg
Base Configuration with BR Booklet Maker Finisher and C-fold/Z-fold Unit	Width: 1,632 mm Depth: 723 mm Height: 1,130 mm Weight: 254.3 kg				Width: 1,632 mm Depth: 723 mm Height: 1,169 mm Weight: 270.9 kg
Base Configuration with BR Booklet Maker Finisher, C-fold/Z-fold Unit and High Capacity Feeder	Width: 2,361 mm Depth: 723 mm Height: 1,130 mm Weight: 285.2 kg				Width: 2,361 mm Depth: 723 mm Height: 1,169 mm Weight: 302 kg
System Certifications/Regu	latory Compliance				
Certifications	To view the latest list of certifi	ications, go to xerox.com/Offic	ceCertifications		

Paper Handling	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Single-Pass Duplex Automo	atic Document Feeder (DADF	·)			
Capacity ⁴	130 sheets				250 sheets
Speed (Up to)	82 ppm black-and-white and 141 ipm black-and-white and				135 ppm black-and-white and colour (simplex) 270 ipm black-and-white and colour (duplex)
Paper Sizes Sensed	85 x 125 mm to 297 x 432 m	nm			
Weights	60 to 128 gsm				
Bypass Tray (Standard)					
Capacity ⁴	100 sheets				
Sizes	Custom Sizes: 89 x 98 mm t	o 320 x 1320 mm (SEF); 0	ptional: Long Sheet Feed Kit ((Banner Printing)	
Weights	52 to 300 gsm, Long sheets	/banners (>483 mm): 106	- 220 gsm		
	Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Leavyweight Glossy Card Stock Lightweight Card Stock Reloa Lightweight Glossy Card Stock Card Stock Recycled Transparencies Long Sheets/Banners: Card Stock Card Stock Card Stock Lightweight Card Stock	ock ock Reloaded aded ck ck Reloaded			
Trays 1 and 2 (Standard)					
Capacity ⁴	520 sheets each				
Sizes	Tray 1: Custom Sizes: 140 x Tray 2: Custom Sizes: 140 x		(SEF)		
Weights	52 to 300 gsm				
Mediα Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Lightweight Card Stock Lightweight Card Stock Lightweight Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Plain Plain-Reloaded Preprinted Recycled Transparencies	ock ock Reloaded aded ck			

Paper Handling (continued)	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170		
Four Tray Module (Trays 3 o	and 4) (Available on C8130/C8135)						
Capacity ⁴	Tray 3: 520 sheets Tray 4: 520 sheets						
Sizes	Trays 3 and 4: 140 x 182 mm	n to SRA3 mm (SEF)					
Weights	52 to 300 gsm						
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Card Stock Lightweight Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Plain Plain-Reloaded Preprinted Recycled Transparencies	ck ck Reloaded ded					
High Capacity Tandem Tra	y (Available with all models)						
Capacity ⁴	Tray 3: 867 sheets Tray 4: 1,133 sheets						
Sizes	A4, JIS B5, Executive (184 x 2	67 mm) LEF					
Weights	52 to 300 gsm						
Media Types	Bond Card Stock Custom Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted						
Envelope Tray (Optional - R	eplaces Tray 1)						
Capacity ⁴	Up to 60 envelopes						
Sizes	No. 10 Commercial (235 x 10 Custom Sizes: 98 x 148 mm to						
Weights	75 to 90 gsm						
High Capacity Feeder (HCF) (Optional with all models)						
Capacity ⁴	3,000 sheets						
Sizes	Standard Sizes: A4 or B5 LEF						
Weights	52 to 300 gsm						
Total Capacity							
Device Total Capacity ⁴	Four Tray Module: 2,180 shee Four Tray Module with High C High Capacity Tandem Tray N High Capacity Tandem Tray N	apacity Feeder: 5,180 sheets lodule: 3,140 sheets	der: 6,140 sheets				

Finishing	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170			
Output Trays (Standard) (D	ı ual Offset Catch Trays not av	ailable with Integrated	ι Office Finisher and limited to	one with Office Finisher an	d BR Finishers)			
Stacking Tray Capacity ⁴	Dual Offset Catch Tray: Up to 250 sheets each Left Side Face up Tray: Up to 100 sheets							
Integrated Office Finisher (ptional with AltaLink® C8130/C8135/C8145/C8155)							
Stacking Tray Capacity ⁴	500 sheets of 80 gsm – A4 or	250 sheets of 80 gsm – A	3					
Sizes	89 x 98 mm to 297 x 432 mm	ı						
Weights	52 to 300 gsm							
Stapling			n 90 gsm or (2) 220 gsm covers) ess than 90 gsm or (2) 220 gsm					
Office Finisher (Optional)								
Stacking Tray Capacity ⁴	2,000 sheets unstapled or 1,0	00 sheets single-stapled o	r 750 sheets dual-stapled (A4)					
Stacking Tray Sizes	210 x 182 mm to 297 x 432 n	nm						
Weights	52 to 300 gsm							
Multiposition Stapling			ı 90 gsm or (2) 220 gsm covers) ess than 90 gsm or (2) 220 gsm					
Hole Punch (Optional)	North America: 2/3-hole pun Europe: 2/4-hole punch Optional: 4-hole "Swedish" pu							
Booklet Maker for Office Fi	nisher (Score/Crease, Saddle-s	stitch Staple) (Optional)						
Top Tray Capacity ⁴	40 booklets (2-15 sheets per b	pooklet – 80 gsm or less)						
Sizes	Letter/A4 SEF Legal/B4 SEF Tabloid/A3 SEF							
Saddle-Stitch Stapling	2-15 sheets/8-60 page bookle 60 to 256 gsm	t						
Score/Crease	1-15 sheets/unstapled 60 to 105 gsm							
Business Ready (BR) Finishe	er (Optional) (Requires Horizo	ntal Transport Kit)						
Capacity ⁴	Offsetting Top Tray: 500 shee Stacking Stapling Tray: 3,000 100 sets (dual or 4-position st	sheets unstapled or	s or 200 sets (single-position sta	ple) A4				
Sizes	100 x 148 mm x 320 x 488 m 182 x 203 mm to 320 x 488 n B5 to A3 for stapling							
Weights	52 to 300 gsm							
Stapling	Single and multiposition stapl Auto stapling (50 sheets maxi Letter, Legal, Tabloid, A3, A4, E	mum) – 90 gsm						
Hole Punch	North America: 2/3-hole pun Europe: 2/4-hole punch Optional: 4-hole "Swedish" pu							
BR Booklet Maker Finisher	(Optional) (Requires Horizont	al Transport Kit)						
Capacity"	Offsetting Top Tray: 500 shee Stacking Stapling Tray: 1,500 sheets of A4/A3 unstap 200 stapled sets of A4 (single dual or 4-position stapling) or	led or position stapling or						
Sizes	100 x 148 mm x 320 x 488 m 182 x 203 mm to 320 x 488 n B5 to A3 for stapling							
Weights	52 to 300 gsm							
Stapling	Single and multiposition stapl Auto stapling (50 sheets maxi Letter, Legal, Tabloid, A3, A4, E	mum) – 90 gsm						
Hole Punch	North America: 2/3-hole pun Europe: 2/4-hole punch Optional: 4-hole "Swedish" pu							
Booklet maker	Saddle-stitch 2 to 16 sheets (7 Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 s	3	n coated or 5 sheets at 177 to 2	220 gsm coated)				

Finishing (continued)	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170	
C-fold/Z-fold Unit (Optiono	ıl with BR Finisher and BR B	ooklet Maker Finisher)				
Types	C-fold, Z-fold and Z-half-fold	d				
Capacity ⁴	40 sheets					
Sizes	C-fold and Z-fold: Letter/A4 Z-half-fold: Tabloid/A3 only	SEF only				
Weights	64 to 90 gsm					
Output Trays	Envelope Tray: C-fold, Z-fold Stacker Tray or Top Tray: Z-h					
Convenience Stapler (Optio	onal - Includes Work Surface	2 ⁵)				
Capacity ⁴	50-sheet stapling 5,000 staples Requires separate power ou	tlet				
Сору	AltaLink® C8130	AltaLink® C8135	AltαLink® C8145	AltaLink® C8155	AltαLink® C8170	
First-Copy-Out Time (from platen/warmed up Colour/Black-and-White)	As fast as 6.1 seconds/ As fast as 4.5 seconds		As fast as 5.5 seconds/ As fast as 4.4 seconds	As fast as 4.7 seconds/ As fast as 3.7 seconds	As fast as 4.0 seconds/ As fast as 3.2 seconds	
Sides (input-output)	1-1, 1-2, 2-2, 2-1		'	'		
Quantity	1 to 9,999					
Resolution (max)	Up to 600 x 600 dpi					
Reduction/Enlargement	Variable zoom from 25% to	400% in 1% increments				
Concurrency	Program-ahead to allow job	to be queued while initial job	is processed (Copy, Print, Fax (and Scan)		
Copy Features	Variable zoom from 25% to 400% in 1% increments Program-ahead to allow job to be queued while initial job is processed (Copy, Print, Fax and Scan) Annotation and Bates™ stamping (with colour capability and font size adjustment) Authentication for Services (i.e. Colour Copy) Auto Paper Select Auto Reduction & Enlargement (to fit selected paper size) Auto Tray Switching Auttomatic 2-sided/Duplex Booklet Creation Build Job (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (front only, front and back, back only, printed inside and out: blank or printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Centre option) Imaging Security Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Colour Stapling Touchless Workflow Accelerators					

Print	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltαLink® C8155	AltaLink® C8170				
Resolution (up to)	1200 x 2400 dpi	1200 x 2400 dpi							
Print Features	Delay Print (specific time) Finishing Fit to New Paper Size Hold All Jobs Image Options (Toner Sat Imaging Security Job Identification (Print II LAN Fax (requires optional Layout/Watermark Long Sheet/Banner N-up (up to 16 pages per Paper Selection by Attribut Print From Cloud Repositat Secure Print with Timed D Special Pages (exception) Store and Recall Driver Se	Colour By Words) Bi-directional User Permissions ver, Resolution (Standard, Enhance) O or Banner, Print ID in marginal Fax Kit) sheet) Ite Sample Set In the Sample Set In t	anced, High)) s on first page only or all page Google Drive) Gerts, exception pages)		Hold All Jobs)				
Print from USB									
Operating Systems	Windows 10 (32 and 64 b Windows 11 (32 and 64 b MacOS 10.13.x, 10.14.x, 1 Red Hat Linux 6.x, 7.x, 8.x Ubuntu Linux 20.04.x, 22. SuSe Linux Server 12.3-13 MS Windows 2012 Server MS Windows 2016 Server MS Windows 2022 Server MS Windows 2022 Server Red Hat Linux Server 7.x, 8 SuSe Linux Server 12.2-12	oit) 0.15.x, 11.0.x, 12.x 04.x .x, 15.x (32 and 64 bit)							
Network Protocols	TCP/IP: HTTP/HTTPS, Inte Microsoft Windows Netw Bonjour®/AirPrint™ IPv6 Most protocols not in use	S), Raw Socket Printing/Port 910	00, IPv4/IPv6, WSD					
Font Capability	PCL: 93 scalable fonts, line	e printer and bitmap font (incl	uding Cyrillic font support) Pos	tScript 3: 173 Type 1 fonts, 2 N	Multiple Master fonts				
Xerox® Global Print Driver®		,			levices from a single driver. It services management. Support				
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others								
Unified Address Book for I	Fax, Email and Scan to								
Features	Services supported: Fax, E Maximum contacts: 5,000 Contacts: Supports 1 or m Favourites for quick access) ore destinations							

Scan	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltαLink [®] C8155	AltaLink® C8170			
Concurrency	Scan while the system is pr concurrent jobs)	Scan while the system is printing or copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)						
Input Speed (up to)	82 ppm black-and-white and colour (simplex) 141 ipm black-and-white and colour (duplex) 135 ppm black-and and colour (simplex) 270 ipm black-and and colour (duplex)							
Resolution	150 x 150 dpi to 600 x 600) dpi						
Bit Depth	1-bit (black-and-white), 8-b	oit (greyscale), 24-bit (colour))					
Maximum Scan Area	A3							
Scan Template Management	Support 250 scan template Create Xerox® CentreWare		re via device cloning to other m	ultifunction printers' confirmati	on sheet options			
Network Protocols	SFTP, FTP, SMB, HTTP, HTT	PS						
File Compression		MH, G4 MMR compression – s PDF/A-1b (MRC, JPEG, G3 MH	single or multiple pages) H, G4 MMR, JBIG 2 Huffman, JB	IG Arithmetic Compression, De	flate (for black-and-white and			
Document Management Fields (Metadata)	• 1 to 6 user-programmab field name, default value	Features only available in Network Scan to File Templates: • 1 to 6 user-programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customised fields viewed on user interface for variable data input						
Scan Features	Auto Background and Shar Bound Originals Compression Quality/File S Edge Erase Imaging Security Mixed Size Originals Scan I Original Type (Photo and T Reduction/Enlargement Scan Preview Single Touch Scan buttons Size for Size (for mixed size Touchless Workflow Accele TWAIN Support/WIA 2.0 S	Guild Job ext, Photo, Text, Map, Newsp (up to 10) originals) rators	aper/Magazine)					
Scan to Email (Standard)								
Scan Features	Auto send to self Email signatures (6 lines sheet options Email signing (requires S Scan to Email S/MIME Er Touchless Workflow Acce	mart Card option) ncryption	email message body (user con	figurable), email Embedded We	eb Server confirmation			
Directory Access	Address list via LDAP (Wind	dows Active Directory, Exchai	nge, Notes, Domino), Device Ac	ldress Book				
Scan To								
Standard Features	Scan to Email Scan to Home Scan to Mailbox Scan to Network (using Ser Scan to Network Folder (us Scan to PC/Server Client (S Scan to PC via USB port Scan to USB	ing Secure FTP/HTTP/HTTPS)					
Optional Features	Native Scan to Cloud Repo	sitories (Dropbox, OneDrive	and Google Drive)³					
Workflow Scanning (Option	nal features)							
Scanning Software	Autostore v7 eCopy ScanStation v5.2 ecopy ShareScan v5.2							
Scanning Apps and Xerox App Gallery		Drive, Microsoft OneDrive, Mi ilable in the Xerox App Galle	crosoft Office 365, Box, Xerox® ry: xerox.com/AppGallery	Workplace Mobile App (iOS/Ar	ndroid)			

Security	AltaLink® C8130	AltaLink® C8135	AltαLink® C8145	AltaLink® C8155	AltaLink® C8170
Features	Audit Log Cisco® Identity Services Eng. Configuration Watchdog (n. 802.1x Admin Password Reset Audit Log Automatic Software Upgr. Email Alerts FIPS 140-3 Hold All Jobs Immediate Job Overwrite Installation Policies Trellix Embedded Control* PII - Login Name PostScript Passwords Remote Services Enablem Remote Start (Mopria® or Remote Start (TWAIN) Reprint Saved Jobs Scan to Mailbox (Internal Scheduled Disk Overwrite Secure Passcode Length Secure Print Device Policie SIEM SNMP System Timeout USB (Print from USB) USB (Scan to USB) USB Port Management User Data Encryption Expanded Authentication Digitally signed PDF (whe Encrypted/Password Prote FIPS 140-3, 256 bit Hard Immediate Image Overw Local Authentication in server 2012), NDS, LDAP or On Demand Image Overw Smart Card authentication Secure Print (up to 10 dig Expanded Authorisation Authorisation per user per SA access based on network Secure Print (up to 10 dig Expanded Authorisation Authorisation per user per SA access based on network Secure Print (up to 10 dig Fills System Common Criter Hide Print Job Names Imaging Security IP Filter, IPsec, IPv6, TLS V1 Trellix Embedded Control* (Port disablement including Security Dashboard	gine (ISE) compatible nonitors and remediates 75 se rade ra	curity settings in the following of Email and Network Scan Templates or 3, IPPS, HTTPS, SFTP, SNMPv3 approved algorithms9 services via Kerberos (UNIX/Windes sanitisation of unused are rt (2048 bit certificate key)/.NE on) ures (e.g. colour access or time Protection Profile for Hardcopy 3, HTTPs, 802.1X, SFTP Control* (optional)	areas): nly) indows Server 2008), SMB (Winea of disk9 :T	dows Server 2008, Windows
Xerox® Integrated RFID				bedded multifunction printer co	ard readers in

Fax	AltαLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170		
Network Server Fax Feature	S	'		'			
Compatibility	TU (CCITT) group 3; Various Xerox® Business Innovation Partner Solutions						
Maximum Scan Area	A3						
Fax Send Features	One- or Two-sided Scanning (Add to Send List (200 numbe Build Job, Favourites, Delay S		e (photo, text or photo and tex	it)			
Fax Print Features	One- or Two-sided Printing, St	taple, Secure Print					
Transmission Resolution	Superfine: 400 x 200 dpi (Sca Fine: 200 x 200 dpi Standard: 200 x 100 dpi	ın at 600 x 600 dpi)					
Walk-up Fax Features (Option	onal; Customer-Installable –	1 and 2 lines)					
Compatibility	ITU (CCITT) Group 3						
Speed/Modems	One or Two V.34 modems: 33	3,600 bps. Less than 4 seconds	per page transmission time				
Compression/Speed	MH/G3, MR/G3, MMR/SG3, JI	BIG/SG3					
Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine Receive: Accepts all sizes	:: 600 x 600 dpi					
Fax Send Features	Automatic Cover Sheets Automatic Memory Resend Batch Send (up to memory co Delay Start, Build Job, Favour Device Address Book (up to 5 LAN Fax (fax from print driver	Automatic Memory Resend Batch Send (up to memory capacity) Delay Start, Build Job, Favourites Device Address Book (up to 5,000 contacts) LAN Fax (fax from print driver) Page-by-page Job Status at the Machine PSTN Fax					
Fax Receive Features	Auto Answer Delay One- or Two-sided Printing Output Tray Selection Receive Print Mode – Manual Receive Timestamp Secure Receive Stapled or Unstapled Up to 200 Password-Protecte	(size, margin, stock, header)/A d Mailboxes	uto				
Fax forward	Forward to Email or SMB Loco Fax Forward on Receive Only	ation					
Fax Reports	Activity, Dial Directory, Group Broadcast Report	Directory, Transmission Confir	mation, Pending Fax, Options F	Report, On Demand Overwrite ⁹	Report, Mailbox Report,		
Directory Access	Utilises the Unified Address B Group fax available	Book					
Auto Redial	Up to 14 attempts (per count 1 to 25 minute intervals	try requirements)					
Auto Resend	Up to 5 attempts						

Device Management		
Administrative Protocols	DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS	
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System-Power MIB, Fleet Orchestrator, Configuration Watchdog, Xerox® Easy Assist App	
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web-browser-based device management from any workstation, whether running on Windows, UNIX or any other operating system: • Works with any SNMP-managed printer from any manufacturer • Remote configuration of SNMP v3 • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management • Requires Windows 7 and Internet Explorer 6.0 and higher • Auto-detect Xerox® CentreWare® Web server and download configurations files for touchless remote install	
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor -across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Remote configuration of SNMP v3 • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities • Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install	
Xerox® Workplace Cloud	Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server	
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files and 1-Touch App files. Auto-assembly feature allows a new AltaLink® to automatically set itself on the network and configure	
Novell NDPS/NEPS	Server gateway application: centralised management tool	
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download. www.xerox.co.uk/en-gb/office/printer-software	
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at www.xerox.co.uk/en-gb/office/printer-software	
Xerox® Embedded Web Serv	rer – Integrated Device Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts • Remote Control Panel	
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard	
Browsers	Microsoft Edge version 88+ Microsoft Chromium Edge version 79+ Mozilla Firefox 91.9.0, 100.0 Safari 13.1.2, 14.1.2, 15.4 Opera 2020, 2021 Google Chrome version 80.0.x+	
Support	Install print/scan drivers and online support available via www.support.xerox.com/en-gb	
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic	
Remote Services		
Xerox [®] Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time	
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for output devices from Xerox based on actual usage, eliminating the need to manually manage supplies inventory	

Accounting				
Xerox® Standard Accounting (Standard)				
Tracking	Copy, Print, Fax, Scan and Email usage			
Accounting	Up to 2,497 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group Accounts (Department)			
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export User Accounts, Group Accounts, General Accounts and User Limits via an industry-standard CSV file 			
Accounting Options – Net	work Accounting (Allows central server to manage all accounting)			
	Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan and server fax Numerous solutions are available through Xerox Alliance Partners. For details, visit www.xerox.co.uk Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third-party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third-party Networking Account Interface with third-party accounting terminal for accounting user interface			
Xerox® EX-c C8100 Print Server Powered by Fiery® (Optional)				
Processor	AMD® GX-424CC processor, 2.4 GHz, Quad-Core, 2M cache			
Memory (ESS)	2 GB			
System Disk	500 GB HDD			
Page Description Language	PostScript v 3020			
Features	Access Controls Automatic two-sided printing Booklet Maker – booklet wizard to create booklets Calibration Digitally Signed Software Updates Expert Colour Settings: Profile, Rendering and Simulation Encryption of critical information Fiery API Fiery Command WorkStation for Mac and Windows clients (customer provided) Fiery drivers for Mac and Windows Fiery FreeForm Create to create personalised files for free Image Enhance IP filtering Integrates with common cost accounting software, Xerox® Standard Accounting, Xerox® App Gallery Apps and more Job Preview Job Presets N-up PANTONE® Colour Enabled Print from USB flash drive PostScript Security Port Blocking Secure Erase Secure Printing Spool-RIP-Print simultaneously Standard support for long sheet banners User Authentication Watermarks			
Connectivity	10Base-T/100Base-TX/1000Base-T Ethernet			
Optional	Fiery Options Bundle (Fiery Spot-On, Auto Trapping, Hot Folders, Virtual Printers), Fiery Hot Folders/Virtual Printers, Fiery Spot-On, Fiery Colour Profiler Suite w/EFI ES-2000 Spectrophotometer, Network Switch to connect both printer and Fiery Server to network			

Supplies	Description	Yield
Toner Cartridge ⁶	Black Cyan Magenta Yellow	59,000 pages 28,000 pages 28,000 pages 28,000 pages
Transfer Belt Cleaner	1 Assembly	160,000 pages
Second Bias Transfer Roll	1 Assembly	200,000 pages
Staple Cartridges	For BR Finisher, Integrated Office Finisher, Office Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge
	For BR Booklet Maker (1 cartridge per carton)	5,000 each cartridge
	For Office Finisher Booklet Maker (8 cartridges per carton)	2,000 each cartridge
Staple Refills	For Integrated Office Finisher, Office Finisher, BR Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill
Fan Filter	1 Assembly (AltaLink® C8170)	500,000 pages
Xerox® Smart Kit®		
Drum Cartridge ⁷	1 Cartridge per Colour	180,000 pages
Waste Toner Container w/o Suction Filter ⁸	1 Cartridge (AltaLink® C8130/35/45/55)	69,000 pages
Waste Toner Container with Suction Filter ⁹	1 Cartridge (AltaLink® C8170)	69,000 pages

Declared in accordance with ISO/IEC 24734.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling programme. For more information, visit www.xerox.co.uk/recycling.

For more information, visit us at www.xerox.co.uk/office.



Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Not available in all geographies.

Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

Sold separately in some geographies

Average standard pages. Declared in accordance with ISO/IEC 19798. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes and image quality set-points.

Average drum yield is based on a run length of 5 pages of A4 LEF pages, with split of 35% colour/65% black-and-white pages.

Waste Toner Container yield will vary depending on type of image, area coverage % and job run length.

⁹ With optional hard drive.
* Trellix DXL formerly known as McAfee® DXL, Trellix Embedded Control Whitelisting formerly known as McAfee® Embedded Control Whitelisting, Trellix ePolicy Orchestrator® formerly known as McAfee® ePolicy Orchestrator®, Trellix ESM formerly known as McAfee® ESM, Trellix Integrity Control Enablement Kit formerly known as McAfee® Integrity Control Enablement Kit, Trellix Enterprise Security Manager formerly known as McAfee® Enterprise Security Manager. Trellix brand name will be reflected in future firmware releases.